

LANmark-OF Sliding Patch Panels

LANmark-OF Patch Panel Snap-In Sliding Black

Contact

Cabling Solutions
Phone: +32 2 363 38 00
info.ncs@nexans.com

Nexans ref.: [N441.204](#)

New fibre optic snap-in patch panel from Nexans, bringing significant improvements resulting in better customer experience when fibre optic networks have to be deployed.

DESCRIPTION

Features

Enhanced sliding mechanism

- System based on wheels enables better opening/closing
- Base plate 100% removable improving installation practices

Reinforced front fixation

- 3 possible positions for the front: flush, flat or recessed
- Fully stable, no risk of movement when patching

Extended cable management

- Multiple entries to provide maximum flexibility
- Accommodates both cable glands as well as tie-wraps
- 2 Gland sizes: 20mm and 25 for large cables

Improved Splice tray handling

- Dedicated Stud attached to the base plate facilitates installation
- Maximum number of trays: 4 + 1 cover (N890.097)
- Splice tray for heat shrink protectors: N890.095
- Splice tray for Aluminium protectors: N890.096

Professional Better Look and feel: Fully painted in black

Includes four sixpack modules to accommodate 24 SC, 24 MTRJ or 48 LC connectors

Inner sliding to respect bending radius of patch cord.

Compatibility

Suitable for tight buffer cables (direct termination) or Loose tube cables using Splice Cassette. Accommodate perfectly Pre-terminated assemblies by means of bendable plates.

Accepting the entire range of LANmark-OF snap-in adapters: LC, MT-RJ, SC or DSC. Supports up to 48 fibres when Small Form Factors (SFF) adapters are used.



LANmark-OF

STANDARDS

International ISO/IEC 11801

LANmark-OF Sliding Patch Panels

LANmark-OF Patch Panel Snap-In Sliding Black

Contact

Cabling Solutions
Phone: +32 2 363 38 00
info.ncs@nexans.com

Installation

- 1 U
- 19" width
- Delivered with modular sixpack-type faceplate
- Accommodates 24 duplex LC, 24 MT-RJ, 24 single SC or 12 duplex DSC snap-in adapters.
- 2 front positions : flush or recessed
 - when the patch panel is installed "flush" the distance between the back of the panel and the rack is 29.7cm
 - when the patch panel is installed "recessed" the distance between the back of the panel and the rack is 32.1 cm
- Supports use of tie-wraps as well as cable glands

CHARACTERISTICS

Dimensional characteristics

Heightunit	1 U
Width	19 in
Depth	310 mm